

BASED ON THE DECREE NO. 305/2011 OF EUROPEAN PARLIAMENT AND OF THE COUNCIL

1.	. Unique identification code of the	81282
	product type	Name of product: POLYLACK F
2.	Type and batch numbers	As given on the declaration of conformity of the product
3.	Intended uses	As given in the ETA - 18/0171 of 30/09/2021 and in ETA - 17/1040 of 19/06/2019 3.1 POLYLACK F is a fire protective and sealing product, white, one-component, water-based, intumescent paint, in a form of a viscous liquid. It is used as a coating and supplied in buckets. 3.2 The intended use of POLYLACK F is to reinstate the fire resistance performance of flexible wall, rigid wall or rigid floor constructions where they are penetrated by combustible pipes, insulated metal pipes, single cables or cable bundles.
4.	Name and contact address of the manufacturer	MERCOR DUNAMENTI Zrt. 2131 Göd, Nemeskéri Kiss Miklós utca 39.
5.	Authorised representative	Not applicable
6.	System or systems of Assessment and Verification of Constancy of Performance (AVCP)	SYSTEM (1) See table under section 9.
7.	The construction	product is not covered by a harmonised standard (hEN)
8.	The declaration of performance concerns construction product for	For the fire protective product POLYLACK F an ETA has been issued by Instytut Techniki Budowlanej (ITB, Poland) with No. ETA-18/0171 of 30/09/2021 and ETA has been issued by FIRES Sro. (FIRES, Batizovce) with No. ETA-17/1040 of 19/06/2019. The ETA's have been issued according to the EAD 350454-00-1104
	which a European Technical Approval has been issued	Notified product certification bodys: ITB No. 1488 and FIRES No. 1396 Certificate of Constancy of Performances: 1488-CPR-0680/W and 1396- CPR-0158

Essential characteristics	AVCP systems	Performance	Harmonise technical specificatio
Mechanical resistance and stability (BWR 1)	Not applie	cable	
Safety in case of fire (BWR	2)		
Reaction to fire	1	Class E	ETA-18/017 of 30/09/202 and ETA-17/104 of 19/06/201 EAD 350454 00-1104
Resistance to fire	1	Annex C of ETA-18/0171 of 30/09/2021 and Annex C of ETA-17/1040 of 19/06/2019 This characteristic depends on the tested set. The performance of the product is determined and analysed according to the principles defined in EN 1366-3/2009 and provided by the manufacturer in accordance with the intended use in part 3 of this document. The classes of performance are established and declared in an assessment document in accordance with the applicable part of EN 13501.	ETA-18/0171 of 30/09/2021 and ETA-17/1040 of 19/06/2019
Hygiene, Health and the Env	vironment ((BWR 3)	
Air permeability	-	NPD (No Performance Declared)	
Water permeability	-	NPD (No Performance Declared)	
Release of dangerous substance		The applicant has submitted a written declaration that the products and/or constituents of the products contain no substances which have been classified as a dangerous according to EOTA TR 34. Regarding the dangerous substances, there may be	ETA-18/0171 of 30/09/2021 and ETA-17/1040 of 19/06/2019 EAD 350454- 00-1104

MD C)	Detembre	Energy Economy and Heat
NPD (No Performance Declared)	-	Airborne sound insulation:
	WR 5)	Protection against noise (B
Use category: Type Z₂	1	Basic durability assessment:
NPD (No Performance Declared)	-	Adhesion:
NPD (No Performance Declared)	-	Resistance to impact and movement:
NPD (No Performance Declared)	use (BWR	Safety and accessibility in Mechanical resistance and stability:
requirements applicable to the products falling within its scope (e.g. transposed European legislation and national laws, regulations and administrative provisions). In order to meet the provision of the Construction Products Regulation, these requirements need also to be complied with when and where they apply.	uso (RWP	Safatu and accessibility in

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Tibor Sebestyén Executive Director

Göd, 30. September 2021.

